Raise/Lower Equipment Using Power Tailgate

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Pinch points	CSA foot wear	
Slips/trips	Hard hats	
Tailgate failure	High Vis Vests	
Contact with machine		

Safe Work Procedure:

- 1) Confirm capacity and total weight
- 2) Make sure truck is sitting straight and not on a large angle
- 3) Ensure that the parking brake is on
- 4) Using minimum of two persons place item on tailgate
- 5) Lower the item onto the tailgate so that it cannot role
- 6) Secure item onto tailgate
- 7) Clear area below gate and or tape off area for lift
- 8) Engage lift gate to level position and elevate/lower piece completely to top or bottom of lift.
- 9) Remove piece from gate with two people

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards:	This Safe Work Procedure will be reviewed any time
	the task, equipment or materials change and at a
MB Workplace Safety & Health Act & Regulations:	minimum of every three years
	Reviewed By WSH Committee:
	Date: