Tilt Trailer Loading/Unloading

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Slip/Trip hazard	Steel toed boots Operator training/certific	
Fall injury	Eye protection	
Vehicle/Machine damage	Hi Visibility Vest	
Pinch points	Hand Protection	

Safe Work Procedure:

- 1) Reverse this procedure for loading
- 2) Block between all trailer wheels
- 3) Ensure the parking brake is always used when loading and unloading to stop movement of the unit
- 4) Back the unit up until the trailer touches the ground
- 5) Shut the truck off and leave in gear so it does not roll
- 6) Take boomers and chains off
- 7) Drive the equipment off the trailer
- 8) If unloading more than one piece of equipment, they must come off at the same time

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards:	This Safe Work Procedure will be reviewed any
MB Workplace Safety & Health Act &	time the task, equipment or materials change
Regulations:	and at a minimum of every three years
4 General Workplace Requirements	Reviewed By WSH Committee:
6 Personal Protective Equipment	
16 Machines, Tools and Robots	Date:
22 Powered Mobile Equipment	