Unloading Crawler Loader from Trailer

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:	
Vehicle or property damage	Steel toed boots	Equipment training/certification	
Slip/Trip Hazards	Eye protection		
Pinch points	Hand protection		
	Hard Hat		
	ROPS		

Safe Work Procedure:

- 1) Park truck and trailer on level ground and set parking brakes.
- 2) Exit vehicle using three point contact
- 3) Set ramps
- 4) Remove chains/binders from machine and unplug exhaust
- 5) Mount trailer using caution and enter machine using 3 point contact method
- 6) Release brake and raise bucket or attachments just above the deck so as to not flip backwards
- 7) Slowly back off of the trailer and park in secure level area
- 8) Load ramps onto the trailer

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards:	This Safe Work Procedure will be reviewed any time the task, equipment or materials change and at a
MB Workplace Safety & Health Act & Regulations:	minimum of every three years
4 General Workplace Requirements 6 Personal Protective Equipment 16 Machies, Tools and Robots	Reviewed By WSH Committee:
22 Powered Mobile Equipment	Date: