Unloading Granular Using Truck

Facility:	Written By:	Approved By:	Date Created:	Date of Last Revision

Hazards Present:	PPE or Devices Required:	Additional Training Required:
Vehicle or property damage	Steel toed boots	
Serious injury	Eye protection	
Pinch points	Hand protection	
	Reflective vest	
	ROPS	

Safe Work Procedure:

- 1) Back up to the dumping location with the use of a spotter
- 2) Park and ensure brake is applied
- 3) Exit cab using three point contact and inspect the ground to ensure it is level and firm
- 4) Roll up tarp
- 5) Enter cab using three point contact
- 6) Engage PTO and pump
- 7) When hoist is lifting, trip the end gate
- 8) Hoist box to the final stage
- 9) When load is dumped slowly drive ahead a few feet and lower hoist
- 10) Disengage pump and PTO and close end gate.

If an emergency situation occurs while conducting this task, or there is an equipment malfunction, engage the emergency stop and follow the lock out procedure

REPORT ANY HAZARDOUS SITUATIONS TO YOUR SUPERVISOR

Guidance Documents/Standards:	This Safe Work Procedure will be reviewed any
MB Workplace Safety & Health Act & Regulations:	time the task, equipment or materials change and at a minimum of every three years
2.1 Safe Work Procedures4 General Workplace Requirements16 Machines, Tools and Robots	Reviewed By WSH Committee:
22 Powered Mobile Equipment	Date: